

Odessa, TX
Office 432-337-1111
Toll Free 855-337-1112
Fax 432-337-5700
2508 South Highway 385
www.platinumpiperentals.com



3-1/2" 13.30# S-135 DRILL PIPE WITH 3-1/2" IF CONNECTIONS

Pipe Body O.D.	(in)	3.500
Nominal Pipe I.D.	(in)	2.764
Nominal Weight Designation		13.30
Drill Pipe Adjusted Weight	(lbs./ft.)	15.30
Pipe Body Grade		S-135
Pipe Body Wall Thickness	(in)	0.368
API Class - Tube		Premium
Pipe Body Tensile	(lbs.)	381,900
Pipe Body Torsional	(ft./ lbs.)	25,900
Pipe Body Collapse	(psi)	21,626
Pipe Body Internal Yield / Burst	(psi)	22,711
Pipe Body Displacement Est. (Includes TJ's)	(bbls/ft.)	0.0056
Pipe Body Capacity Est. (Includes TJ's)	(bbls/ft.)	0.0071
Connection Type		3-1/2" IF
Connection O.D.	(in)	4.875
Connection I.D.	(in)	2.563
Tool Joint Drift	(in)	2.438
Recommended Make Up Torque (Max)	(ft./ lbs.)	12,100
Minimum Make Up Torque	(ft./ lbs.)	10,000
Tool Joint Torsional Strength	(ft./ lbs.)	20,100
Tool Joint Tensile Strength (At Rec. MUT)	(lbs.)	634,700

The technical information herein is for reference only and should not be construed as a recommendation. The user should consider all field conditions along with other combined factors which may effect the final string design used in the field. Combined loads, slip crushing, elevator hoisting capacity, ID Coatings, and Hardbands are not considered in these figures.

Capacity / Displacement and adjusted weight figures are based upon pipe purchased at above standard RBW and with longer than standard tool joints. All dimensions are nominal. Figures are subject to change without notice. Please refer to our website for updates. www.platinumpiperentals.com