

Odessa, TX
 Office 432-337-1111
 Toll Free 855-337-1112
 Fax 432-337-5700
 2508 South Highway 385
 www.platinumpiperentals.com



Drill Pipe Specification Data

4" 14.00# S-135 DRILL PIPE WITH XT39 CONNECTIONS

Pipe Body O.D.	(in)	4.000
Nominal Pipe I.D.	(in)	3.340
Nominal Weight Designation		14.00
Drill Pipe Adjusted Weight	(lbs./ft.)	16.38
Pipe Body Grade		S-135
Pipe Body Wall Thickness	(in)	0.330
API Class - Tube		Premium
Pipe Body Tensile	(lbs.)	403,500
Pipe Body Torsional	(ft./ lbs.)	32,800
Pipe Body Collapse	(psi)	13,836
Pipe Body Internal Yield / Burst	(psi)	17,820
Pipe Body Displacement Est. (Includes TJ's)	(bbls/ft.)	0.0060
Pipe Body Capacity Est. (Includes TJ's)	(bbls/ft.)	0.0102
Connection Type		XT39
Connection O.D.	(in)	4.875
Connection I.D.	(in)	2.563
Tool Joint Drift	(in)	2.438
Recommended Make Up Torque (Max)	(ft./ lbs.)	22,200
Minimum Make Up Torque	(ft./ lbs.)	18,500
Tool Joint Torsional Strength	(ft./ lbs.)	37,000
Tool Joint Tensile Strength (At Rec. MUT)	(lbs.)	724,100

The technical information herein is for reference only and should not be construed as a recommendation. The user should consider all field conditions along with other combined factors which may effect the final string design used in the field. Combined loads, slip crushing, elevator hoisting capacity, ID Coatings, and Hardbands are not considered in these figures.

Capacity / Displacement and adjusted weight figures are based upon pipe purchased at above standard RBW and with longer than standard tool joints. All dimensions are nominal. Figures are subject to change without notice. Please refer to our website for updates.
 www.platinumpiperentals.com